



Off Road Vehicles

AM200 MINIBUS

There are places where a minibus or a standard microbus cannot arrive. For these situations, Agrale developed Marruá AM200 Microbus, the utility targeted to the passenger transport market that faces any hurdle. Marruás AM200 has been specially designed to operate in extreme conditions. With features derived from military models, such as the strong and robust powertrain, the wide suspension system and strength of the assembly, Agrale Marruá is the ideal vehicle for transporting people in hard place to reach.



**PARTS &
SERVICES**



WARRANTY AGRALUB



@f00in agraleSA
www.agrale.com.br

AM200 MINIBUS



BODY	
Cab	11 Passengers Driver + 10 passengers
ELECTRIC SYSTEM	
Voltage Battery	12 V / 95 Ah
DRIVING TRANSMISSION	
Make/Model	EATON ESO 6205 (manual) ALLISSON LCT1000 XFE (Automatic)
No. of Gears	5 forward / 1 reverse (manual) 6 forward / 1 reverse (automatic)
SUSPENSION	
Front	Longitudinal and transverse bars (with panhard rod) and helical springs
Rear	Semi-elliptical leaf spring
Front/Rear Shock Absorbers	Double action, Telescopic
THEORETICAL PERFORMANCE	
Ignition on Ramp in TGW (Start Ability)	39,4%(21,3°)
WHEELSETS	
Model	8.00 x 16"
BRAKES	
Service Brake - Type	Electronically assisted disc brakes on all 4 wheels (ABS/EBD)
Actuation	Hydraulic servo-assisted with ABS/EBD
WEIGHTS AND CAPACITIES	
TGW - Total Gross Weight	4.300 Kg
MTC - Maximum Traction Capacity	8.100 Kg
Kerb weight	3.500 Kg
Maximum Load of Front Axle	
Maximum Load of Rear Axle	
OPTIONALS	
Electric Lock , Electric Wich, Electric Window Control , Electronic Recording Tachometer, GPS, Inclinator, Kit Tire LT 265/75R16, Seat 2/3 - Fabric, Shovel/Axe Set, Snorkel, Tow coupling	

ENGINE	
Make/Model	Cummins F3.8
Emissions Control	Common Rail
Cylinders / displacement	4 in line
Power	125 kW (170 cv) @ 2.600 rpm
Torque	600 Nm @ 1.200 – 1.900 rpm
CLUTCH	
Type	Organic - Dry sigle disc
TRANSFER CASE	
Ration	Agrale: 1:1
Model	Manual / 2 speeds
TRACTION AXLE	
Front	Agrale 8.9
Ratio - Front	4,10 : 1
Rear	DANA 70
Ratio - Rear	4,10 : 1
STEERING WHEEL	
Model	TRW TAS 20 314
TIRES	
Model	ATR 265 / 75 R16
SUPPLY CAPACITY	
Fuel Tank (Diesel S50)	100 L
Urea Tank (Arla 32)	16 L
FEATURES	
Air Conditioner , Bull Bar, Fog Lights, Headrest , Heating System, Individual Seat - Vinyl, Lights Protectors, Running Boards, Skid Plate	

