



AGRICULTURAL TRACTORS **TRACTOR 6185**

High performance, convenience and durability are some of the differentials that make Tractor 6185 an excellent option for field routine, especially in scale agriculture.



**PARTS &
SERVICES**



WARRANTY AGRALUB



@f00in agraleSA
www.agrale.com.br

TRACTOR 6185

ENGINE	
Brand	MWM 229-6 TCE
No. of Cylinders	6 - Vertical in line / 6.200 cm³
Aspiration	Turbo
Power	175 cv
Maximum Power in PTO	NI
Maximum Torque	72 Kgf.m @ 1.300 - 1.500 rpm
CLUTCH	
Type	Simple disc
Drive	Mechanical
HYDRAULIC SYSTEM	
Pressure	180 kgf/cm²
Maximum Flow	126 L/min
Remote control	4 ways double command Opcional: 1 control remoto de flujo continuo
Hitch	3 Points - Category III
Lift capacity	6.700 kg
STEERING WHEEL	
Type	Hydrostatic
ELECTRIC SYSTEM	
Battery	12 V – 135 A.h
Alternator	14 V – 120 A
DIMENSIONS	
Width	2670 mm

DRIVING TRANSMISSION	
Type	Synchronized mechanical
No. of Gears	24 Front /12 Reverse
Front axle	Limited slip center differential (4WD)
POWER TAKEOFF	
Drive	Electro-hydraulic
Type	Independent, with multidisc wet clutch
Nominal Speed	540 rpm @ 2083 engine rpm and 1000 rpm @ 2136 engine rpm
BRAKES	
Service Brake	Wet disc oil bath
WHEELSETS	
Standard Front Tires	18.4 – 26" R1
Standard Rear Tires	24.5 – 32" R1
Optional Weelsets	Muddy soil tires 14.9 – 28 R2 / 23.1 – 30 R2 Row crop tires 18.4-26/20.8-38 Double Rear Wheel 18. 4-26R1-20.8-38R1 Land farm tires 16.9-30R1/24.5-32R1 14.9-28R1 / 23.1-30R1
CAPACITIES	
Fuel Tank	280 L
WEIGHTS	
Shipping weight	7.020 kg
Operating weight (curb weight)	9.500 kg

