

AGRICULTURAL TRACTORS

TRACTOR 6185

High performance, convenience and durability are some of the differentials that make Tractor 6185 an excellent option for field routine, especially in scale agriculture.

PARTS & SERVICES

WARRANTY

AGRALUB

agraleSA
www.agrale.com.br

TRACTOR 6185

ENGINE	
Brand	MWM 229-6 TCE
No. of Cylinders	6 - Vertical in line / 6.200 cm³
Aspiration	Turbo
Power	175 cv
Maximum Power in PTO	NI
Maximum Torque	72 Kgf.m @ 1.300 - 1.500 rpm
CLUTCH	
Type	Simple disc
Drive	Mechanical
HYDRAULIC SYSTEM	
Pressure	180 kgf/cm²
Maximum Flow	126 L/min
Remote control	4 ways double command Opcional: 1 control remoto de flujo continuo
Hitch	3 Points - Category III
Lift capacity	6.700 kg
STEERING WHEEL	
Type	Hydrostatic
ELECTRIC SYSTEM	
Battery	12 V – 135 A.h
Alternator	14 V – 120 A
DIMENSIONS	
Width	2670 mm

DRIVING TRANSMISSION	
Type	Synchronized mechanical
No. of Gears	24 Front /12 Reverse
Front axle	Limited slip center differential (4WD)
POWER TAKEOFF	
Drive	Electro-hydraulic
Type	Independent, with multidisc wet clutch
Nominal Speed	540 rpm @ 2083 engine rpm and 1000 rpm @ 2136 engine rpm
BRAKES	
Service Brake	Wet disc oil bath
WHEELSETS	
Standard Front Tires	18.4 – 26" R1
Standard Rear Tires	24.5 – 32" R1
Optional Weelsets	Muddy soil tires 14.9 – 28 R2 / 23.1 – 30 R2 Row crop tires 18.4-26/20.8-38 Double Rear Wheel 18. 4-26R1-20.8-38R1 Land farm tires 16.9-30R1/24.5-32R1 14.9-28R1 / 23.1-30R1
CAPACITIES	
Fuel Tank	280 L
WEIGHTS	
Shipping weight	7.020 kg
Operating weight (curb weight)	9.500 kg

This brochure is for informational purposes only. Agrale, or the proposer, may offer products with characteristics different from those described herein. For the definitive document of the offer, the Commercial Proposal signed by the legal representative of the offering company shall prevail. Generated on: 01/20/2026, 11:00 Gerado em: 15/11/2026, 16:03