

AGRICULTURAL TRACTORS

TRACTOR 575 COMPACT

The 575 Compact retains all the attributes that have enshrined it to the farmers, such as economy, versatility and robustness, besides bringing improvements that make it more modern and superior in performance.

PARTS & SERVICES

WARRANTY

AGRALUB

agraleSA
www.agrale.com.br

TRACTOR 575 COMPACT

ENGINE	
Brand	PERKINS 1104D
No. of Cylinders	04 Vertical in line / 4.400 cm³
Aspiration	Natural
Power	76,1 cv (55,9 kW) - 2.200 RPM (SAE J1995)
Maximum Torque	26,6 kgf.m (261 N.m) @ 1.700 rpm
CLUTCH	
Type	Double dry disc
Drive	Mechanical
HYDRAULIC SYSTEM	
Pressure	180 kgf/cm²
Maximum Flow	50 L/min
Remote control	2 way single command Standard with fast coupling and two pressure lines
Hitch	3 Points Category II
Lift capacity	2.000 kg
STEERING WHEEL	
Type	Hydraulic, hydrostatic
ELECTRIC SYSTEM	
Battery	12 V / 70 A
Alternator	12 V / 85 A
DIMENSIONS	
Width	1.430 mm
OPTIONAL ITEMS	
Folding rear arch; Two rear weights;	

DRIVING TRANSMISSION	
Type	Synchronized mechanical
No. of Gears	Reverser and creeper 15 forward and 15 reverse
Differential lock	Mechanical foot pedal and automatic disengaging
Front axle	Center differential (4WD)
POWER TAKEOFF	
Drive	Mechanical
Type	Independent
Nominal Speed	540 to 2000 engine rpm 540 (Eco) at 1600 engine rpm
BRAKES	
Service Brake	Wet disc oil bath
Parking Brake	Manual lever
WHEELSETS	
Standard Front Tires	250/80 x 18R1
Standard Rear Tires	14.9 x 24R1
CAPACITIES	
Fuel Tank	70 L
WEIGHTS	
Shipping weight	2.370 Kg (without cabin) 2.590 Kg (with cabin)
Operating weight (curb weight)	3.150 Kg (without cabin) 3.315 Kg (with cabin)

This brochure is for informational purposes only. Agrale, or the proposer, may offer products with characteristics different from those described herein. For the definitive document of the offer, the Commercial Proposal signed by the legal representative of the offering company shall prevail. Generated on: 01/20/2026, 11:11 Gerado em: 09/11/2026, 13:56