

AGRICULTURAL TRACTORS

TRACTOR 4125

The 4125 tractor combines strength and high performance to ensure maximum productivity in your farm's day-to-day operations. Synonymous with quality and strength, it provides greater safety and confidence for you to sow and reap good results.

PARTS & SERVICES

WARRANTY

AGRALUB

agraleSA

www.agrale.com.br

TRACTOR 4125

ENGINE	
Brand	AGRALE YD390T
No. of Cylinders	3 / 1532 cm³
Power	25,0 cv (18,4 kW) a 2.400 rpm
Maximum Torque	9,43 kgf.m (92 N.m) / 1.600 RPM (NBR ISO 1585)
CLUTCH	
Type	Simple dry disc
Drive	Mechanical
HYDRAULIC SYSTEM	
Pressure	120 kgf/cm²
Maximum Flow	36 L/min @ 2.400 engine rpm
Remote control	(Optional) 2 way single command
Hitch	3 Points - Category 1
Lift capacity	650 Kg
WHEELSETS	
Standard Front Tires	6.5/80 - 12
Standard Rear Tires	8.3x24 R1
CAPACITIES	
Fuel Tank	26 L
WEIGHTS	
Shipping weight	1.440 Kg
Operating weight (curb weight)	1.730 Kg

DRIVING TRANSMISSION	
Type	Mecanic
No. of Gears	7 Front/ 3 Forward
Differential lock	Mechanical actuation auxiliary lever
Front axle	Directional traction (central differential)
POWER TAKEOFF	
Drive	Mecanic
Type	Dependent
Nominal Speed	540/750/1000 rpm
STEERING WHEEL	
Type	Hydrostatic
ELECTRIC SYSTEM	
Battery	12 V / 55 Ah
Alternator	14 V / 35 A
DIMENSIONS	
Width	1.280 mm
Length	2.810 mm
Height	2.025 mm
Front gauge	955 mm
Rear Tread	1.000 mm

This brochure is for informational purposes only. Agrale, or the proposer, may offer products with characteristics different from those described herein. For the definitive document of the offer, the Commercial Proposal signed by the legal representative of the offering company shall prevail. Generated on: 01/20/2026, 15:07 Gerado em: 09/11/2026, 13:58