



Industrial

TRACTOR 4100 INDUSTRIAL

The Industrial Tow Tractor 4100 is equipped with a 15 hp engine that provides for low maintenance costs. Ideal for moving cargo and materials in airports, condominiums, hospitals, and logistics and industrial operations.



**PARTS &
SERVICES**



WARRANTY AGRALUB



@f i n agraleSA
www.agrale.com.br

TRACTOR 4100 INDUSTRIAL



ENGINE	
Brand	AGRALE
No. of Cylinders	1 - Vertical
Aspiration	Natural
Power	14,7 cv (10,8 kW) / 2.750 rpm
Maximum Power in PTO	13,2 cv (9,7 kW) @ 2.750 engine rpm
Maximum Torque	3,9 daNm - 4,0 kgf.m @ 2.350 rpm (NBR ISO 1585)
CLUTCH	
Type	Simple dry disc
Drive	Mechanical
HYDRAULIC SYSTEM	
Pressure	NA
Maximum Flow	NA
Remote control	NA
Hitch	NA
Lift capacity	NA
STEERING WHEEL	
Type	Hydrostatic
ELECTRIC SYSTEM	
Battery	12 V – 55 Ah
Alternator	14 V – 55 A
DIMENSIONS	
Width	1.220 mm
Length	2.410 mm
Height	1.210 mm
Front gauge	797 mm / 925 mm
Rear Tread	863 mm / 976 mm
OPTIONAL ITEMS	
Rear wheels weights, low seat kit, front guard, optional industrial draw bar, canopy, beacon light, remote control valve.	

DRIVING TRANSMISSION	
Type	Mecânica
No. of Gears	7 Front /3 Reverse
Differential lock	NA
Front axle	Oscillating
POWER TAKEOFF	
Nominal Speed	1.300 rpm @ 2.750 engine rpm 1.000 rpm @ 2.750 engine rpm (4th and low range) 1.420 rpm @ 2.750 engine rpm (Reverse)
BRAKES	
Service Brake	With expandable shoes
Parking Brake	Manual Lever
WHEELSETS	
Standard Front Tires	5,60 x 15" F3
Standard Rear Tires	7,50 x 18"
Optional Weelsets	Double rear wheels
CAPACITIES	
Fuel Tank	19,6 L
WEIGHTS	
Shipping weight	910 kg
Operating weight (curb weight)	1.000 kg
Load Capacity	NA

