Off Road Vehicles

AM250 SIMPLE CAB

An 4x4 vehicle prepared for different missions.

The Agrale Marruá AM250 Single Cab was designed to deliver capability, durability and 4x4 mobility in demanding operating conditions.

Its configuration allows for cargo transportation and the installation of different bodies and implements, making it a versatile solution for applications such as mining, forestry, utility maintenance, sanitation and emergency services.

AM250 SIMPLE CAB

BODY	
Cab	2 seats
Dump	With metalic bucket Without metalic bucket
ELECTRIC SYSTEM	
Voltage	12 V
Battery	12 V/ 95 Ah
Alternator	12V / 135A
TRANSFER CASE	
Type	Manual / 2-speed (with reduction)
Ration	1,77 :1 / 1.00 :1
TRACTION AXLE	
Front	AGRALE 8.9
Ratio - Front	4.10:1
Rear	DANA 70 Full-floating axle with “POWER LOCK” differential lock
Ratio - Rear	4.10:1
WHEELSETS	
Model	8.00 x 16"
BRAKES	
Service Brake - Type	Disc brakes on all four wheels, electronically assisted (ABS/EBD)
Actuation	Hydraulic servo-assisted
Parking Brake - Type	Rear actuation | Pedal with cab
WEIGHTS AND CAPACITIES	
TGW - Total Gross Weight	5.700 kg
MTC - Maximum Traction Capacity	5.700 kg
Kerb weight	2.910 (without bucket) 3.095 Kg (with bucket)
Load Capacity	2.825 kg (without bucket) 3.010 kg (with bucket)
Maximum Towing Capacity	2.000 kg
Maximum Load of Front Axle	2.300 kg
Maximum Load of Rear Axle	3.400 kg
OPTIONALS	
Bull Bar, Electric Wich, Fog Lights, Inclinometer, Snorkel, Tow coupling, Kit Multimedia, Comfort and Safety Kit; MTR tires;	
BALLISTIC PROTECTION	
Optional armored configuration, with protection up to NIJ Level III.	

ENGINE	
Make/Model	Cummins F 3.8
Emissions Control	After treatment of gases by selective catalytic reduction (SCR). EURO VI
Cylinders / displacement	4 in line | 3.800 cm³
Power	170 cv (125 Kw) / 2.600 rpm
Torque	600 Nm / 1.200 - 1.900 rpm
Available with Euro 3, Euro 5 or Euro 6 engines, according to the emissions requirements applicable in each country. For further information, please contact your nearest distributor or the factory.	
DRIVING TRANSMISSION	
Make/Model	Alisson LCT 1000 XFE - Automátic EATON ESO 6205 - Manual
No. of Gears	6 Forward | 1 Reverse - Automatic 5 Forward | 1 Reverse - Manual
SUSPENSION	
Front	Longitudinal and transversal bars with panhard, and helicoidal springs
Rear	Semi elliptic springs
THEORETICAL PERFORMANCE	
Maximum Speed	145 km/h - Automatic 134 Km/h - Manual
TIRES	
Model	285/75 R16
SUPPLY CAPACITY	
Fuel Tank (Diesel S50)	95 L
Urea Tank (Arla 32)	16 L
FEATURES	
Air Conditioner , Cruise Control, Headrest , Heating System, Lights Protectors, On-Board Computer, Running Boards, Skid Plate, Daytime Running Light, Hydraulic steering	
OVERALL DIMENSIONS	
Wheelbase	3.530 mm
Overall Vehicle Length	5.574 mm (Without cargo bed) 5.464 mm (With cargo bed)
Maximum Vehicle Width (Mirror to Mirror)	2.530 mm
Maximum Vehicle Height	2.030 mm
Track Width	Front 1.772 mm Rear 1.792 mm
Maximum Width (Outer Tire Face)	Front axle 2.057 mm Rear Axle 2.077 mm
Maximum Width Between Fenders	Cab 2.070 mm Cargo bed 2.160 mm

This brochure is for informational purposes only. Agrale, or the proposer, may offer products with characteristics different from those described herein. For the definitive document of the offer, the Commercial Proposal signed by the legal representative of the offering company shall prevail. Generated on: 09/30/2026, 10:10 Gerado em: 09/11/2026, 13:48